

Northwest Specialty Hardware Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015, USA

Phone: (503)557-1881 Fax: (503)557-1885 sales@northwestsh.com www.northwestsh.com

#### The Leading Manufacturer of Premium Detention Hardware & Accessories

#### Statement on Substitution Proposal Detention Hinges or Door Pulls

NW 645FMST 4.5 inch detention hinge was tested by an independent laboratory and passed ASTM F1758-03 Grade 1 Test in 2002. NW 601 raised pull, NW 602 recessed pull, and NW 701 push pull plate are certified to be in compliance with ANSI/BHMA A156.6 standards.

NW 645FMST hinge and door pulls are specified by architects and accepted by correctional facilities. Northwest Specialty Hardware, Inc. (the "Northwest") has been supplying NW hinges and door pulls to the DECs (Detention Equipment Contractors) since 2002. The DEC's hinges and door pulls specified by architects are NW 645FMST hinge and door pulls, which shall **NOT** be substituted by any poor-quality proposal hinges or door pulls.

If any DEC or Northwest customer intends to replace its specified hinges or door pulls with any proposal hinges or door pulls for bidding, a completed substitution form shall be submitted with samples, tests, and reports for the architect's evaluation and owner's consent. A detailed comparison showing the differences between NW 645FMST hinge or door pulls and the proposed hinges or door pulls shall be submitted for the architect's evaluation.

NW 645FMST hinge is superior to any other brand hinges in the cycle, impact, overloading performance, durability, and corrosion resistance in the correctional industry. The specifications of NW 645FMST hinge are those of Northwest customer's one. The customer is advised to compare the aspects of NW 645FMST hinge and proposal hinge, including (1) processing quality, (2) bearing quality, (3) chemical composition, and (4) corrosion resistance, by cutting the hinges apart for quality inspection.

The chemical composition of the hinge leaf and pin shall be inspected in accordance with 304 stainless steel ASTM standards. The corrosion resistance of the hinge tip, pin, and leaf shall be tested in accordance with ASTM B117 salty spray testing.

There is a clear distinction between NW 645 (645FMST or 645FM) hinge and proposal hinge as follows:

- (1) Northwest adopts unique processing techniques to ensure NW 645 hinge superior function and durability over other brands.
- (2) The anti-friction bearings of NW 645 Hinges are custom-made per our specifications for superior strength, durability, and long life, surpassing other brands.
- (3) Both leaf and pin of NW 645 Hinge are made from 304 stainless steel in accordance with the ASTM standards.
- (4) The hinge tip, pin, and leaf of NW specified hinge is considerably more resistant to corrosion than other brands.

NW detention hinges and door pulls are manufactured by Northwest in our own factory by focusing on the core competency of our corporate groups' expertise in investment casting and forging industry. Each of NW hinges and door pulls is triple checked by our quality control staff for quality assurance. Each of NW hinges and door pulls is insured by Northwest to protect the DEC or customer from product liability claims.



## NW 601 RAISED PULL

Size: 9" long x 2 3/16" Projection

Material: Stainless Steel, Investment Cast

Style: Raised (Loop)

Finish: US32D

Mounting Screws: Security Oval Head

SS 3/8-16 x 3/4"

**Certification:** Meets ANSI/BHMA A156.6

for J401 Pull



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015



### **NW 602**

#### **RECESSED PULL**

**Size:** 4" x 5" x 1" Deep

Material: Stainless Steel, Investment Cast

**Style:** Recessed (Flush)

Finish: US32D

Mounting Screws: Security Flat Hd, SS

1/4-20 x 1/2"

**Certification:** Meets ANSI/BHMA A156.6

for J403 Pull



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015



## NW 603 KNOB PULL

Size: 2 1/4" Dia Knob,

3 1/4" Dia Base,

2 1/4" Projection

Material: Stainless Steel

Style: Knob Finish: US32D

Mounting Screws: Security Flat Hd,

10-24 x 1/2"



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015

Phone (503) 557-1881 Fay (503) 557



### **NW 701**

### **COMBINATION PUSH PULL PLATE**

**Size:** 10 1/4" x 3 1/2" x 0.118" Thick

with 1" Projection

Material: Stainless Steel

**Finish:** US32D Satin Finish **Mounting Screws:** Security Flat Hd, SS

1/4-20 x 1/2"

**Certification:** Meets ANSI/BHMA A156.6

for J303 Plate

**Features:** Specific dimensions meet the detention industry standards. The combination push pull plate protects a detention door when the door is opened and closed.







# NW 706 DETENTION WALL STOP

**Size:** 2 5/8" Dia. x 1 1/4" Projection

Integral 3/8" Dia Anti-Rotation Post

Material: Silicone Rubber Body,Black
Style: Heavy-Duty, Wall Mount
Fastener: 3/8" x 2 1/2" Security Torx BH

Concrete Expansion Anchor

**Mounting:** Embed in Concrete or Cinder Block Walls



*Note:* Also available *NW 706SC* Steel Cell Wall Stop with Security Torx BH Screw 3/8"-16 x 1" for being embed in Steel Cell Walls.



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015 Phone (503) 557-1881 Fax (503) 557-1885 Email: sales@northwestsh.com



# NW 606 DETENTION DOOR STOP

**Size:** 2" Dia. x 3 1/2" Bumper

5/8-11 x 2 1/2" Post

Material: Silicone Rubber Body

w/Threaded Steel Post

Style: Heavy-Duty

Floor or Wall Mount

Finish: Black

**Mounting:** Embed in Concrete or Masonry



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015



### **NW 606S**

## **DETENTION DOOE STOP, SHORT**

**Size:** 2" Dia. x 1 1/2" Bumper

5/8-11 x 2 1/2" Post

Material: Silicone Rubber Body

w/Threaded Steel Post

**Style:** Heavy-Duty

Wall or Floor Mount

Finish: Black

**Mounting:** Embed in Concrete or Masonry



Northwest Specialty Hardware, Inc. 15865 SE 114th Avenue, Suite C Clackamas, OR 97015