



The Leading Manufacturer of Premium Detention Hardware & Accessories

NW 611

BALL TIP, TOILET PAPER HOLDER

Size:	4" x 4" x 4" Projection
Material:	Stainless Steel w/Nylon Insert 14 ga Slope Top Housing
Style:	Front Mounted Collapsible Ball-Joint Ball Tip Lever
Finish:	US32D
Mounting Screws:	Security Flat Hd, 1/4-20 x 2"
Features:	For holding toilet paper Anti-Ligature Design conveniently and easily surface-mounted on wall




NW 611, Ball Tip



NW 611, Flat Tip

Note: NW 611 with Flat Tip Lever also Available



Northwest Specialty Hardware, Inc.
15865 SE 114th Avenue, Suite C
Clackamas, OR 97015
Phone (503) 557-1881 Fax (503) 557-1885 Email: sales@northwestsh.com

www.northwestsh.com



The Leading Manufacturer of Premium Detention Hardware & Accessories


NW 620

RECESSED TOILET TISSUE HOLDER

Overall Size: 6 1/4" dia. x 4 3/4" depth
Internal Size: 5 1/2" dia. x 4 5/16" depth
Material: 16 ga Stainless Steel
Style: Chase Mounted
Finish: Exposed Surfaces in Satin Finish
Features: Forged one-piece seamless construction
Rim of holder beveled to insure tight fit to wall surface

\$26.99

Installation: Back of holder has welded anchor nuts to receive threaded studs.
11 gauge die-formed galvanized steel back plate, reversible for shallow or deep wall installation.



Northwest Specialty Hardware, Inc.
15865 SE 114th Avenue, Suite C
Clackamas, OR 97015
Phone (503) 557-1881 Fax (503) 557-1885 Email: sales@northwestsh.com

www.northwestsh.com



The Leading Manufacturer of Premium Detention Hardware & Accessories

NW 621 RECESSED TOILET TISSUE HOLDER

Overall Size:	7" x 7" x 4 1/2" depth	\$29.99
Internal Size:	5 3/8" dia. x 3 15/16" depth	
Material:	14 ga Stainless Steel Flange 16 ga Stainless Steel Holder	
Style:	Front Mounted	
Finish:	Exposed Surfaces in Satin Finish	
Screws:	Security Button Head, 1/4"-20 x 1" for installation to wall anchors (Not included)	
Features:	Flange welded to holder to ensure a tight fit to wall surface Holder forged one-piece seamless construction	

Requirement: It is required to use a security caulk around the front edge between the flange and the holder for anti-ligature purpose.



Northwest Specialty Hardware, Inc.
15865 SE 114th Avenue, Suite C
Clackamas, OR 97015
Phone (503) 557-1881 Fax (503) 557-1885 Email: sales@northwestsh.com

www.northwestsh.com